





Suitable for moderate noise levels



75L




75Z

DucoGrille Acoustic 75Z & 75L

DucoGrille Acoustic G 75Z & G 75L are sound-absorbing recessed wall louvres manufactured from extruded aluminium sections. One type of louvre blade offers the option of **two different looks**: Z and L. The louvre blades have **sound-absorbing, non-flammable mineral wool** inside.

FRAME TYPES AND DIMENSIONS

Dimensions in mm	G
Louvre pitch	60
Recess depth	82
Frame rebate	48
Min. dimensions	min. W 250 x H 250



G 75Z
Recessed wall louvre
with flange



G 75L
Recessed wall louvre
with flange

SOUND ABSORPTION

Attenuation value Rw (C;Ctr) in dB	
75Z	75L
6 (0;-1)	6 (0;-2)

VENTILATION VALUES

	75Z	75L
Visual free passage	76 %	95 %
Physical free passage	28 %	28 %
Ce (higher is better)	0,24	0,25
Cd (higher is better)	0,21	0,29
K-FACTOR (lower is better)	INLET	16,93 16,52
	OUTLET	21,83 12,14

WATER RESISTANCE

Air velocity	Class	
	75Z	75L
0 m/s	B (97,8%)	B (97,2%)
0,5 m/s	B (95,1%)	C (93,9%)
1 m/s	C (89,4%)	C (88,2%)
1,5 m/s	D (77,3%)	D (75,0%)
2 m/s	D	D
2,5 m/s	D	D

INSECT SCREEN

STANDARD		
Stainless-steel mesh 2.3 x 2.3 mm		
OPTION	Stainless-steel mesh 6 x 6 mm	
	Stainless-steel mesh 20 x 20 mm	