




High Performance




Excellent water resistance



DucoGrille Classic 130HP


The DucoGrille Classic 130HP has been specially developed for **intensive ventilation**. The uniquely shaped 'High Performance' louvre blade with a low resistance factor provides a combination of **very good airflow** together with **excellent water resistance (class A)**. All types are manufactured from extruded aluminium sections. Insect mesh is fitted as standard.

water resistance
CLASS A
up to 2.5 m/s




FRAME TYPES AND DIMENSIONS

Dimensions in mm	G	N
Louvre pitch	50	
Recess depth	158	165
Frame rebate	48	0
Min. dimensions	min. W 250 x H 250	



G 130HP
Recessed wall louvre
with flange



N 130HP
Recessed wall louvre
without flange

VENTILATION VALUES

Visual free passage	88 %	
Physical free passage	70 %	
Ce (higher is better)	0,34	
Cd (higher is better)	0,27	
K-FACTOR (lower is better)	INLET	8,55
	OUTLET	13,42

WATER RESISTANCE

Air velocity	Class
0 m/s	A
0,5 m/s	A
1 m/s	A
1,5 m/s	A
2 m/s	A
2,5 m/s	A

INSECT SCREEN

STANDARD	Stainless-steel mesh 2.3 x 2.3 mm	
OPTION	Stainless-steel mesh 6 x 6 mm	
	Stainless-steel mesh 20 x 20 mm	