




Good water resistance Penetration safety




DucoGrille Classic 70V

DucoGrille Classic G 70V is a recessed wall louvre manufactured from extruded aluminium sections. Insect mesh is fitted as standard. The unique “V”-shaped blade ensures better water resistance and makes the louvre grille ‘penetration-proof’ and difficult to see through from the outside.

FRAME TYPES AND DIMENSIONS

Dimensions in mm		G
Louvre pitch		65
Recess depth		82
Frame rebate		48
Min. dimensions	min. W 300 x H 300	



G 70V
Recessed wall louvre
with flange

VENTILATION VALUES

Visual free passage		65 %
Physical free passage		36 %
Ce (higher is better)		0,12
Cd (higher is better)		0,11
K-FACTOR (lower is better)	INLET	72,79
	OUTLET	83,88

WATER RESISTANCE

Air velocity	Class
0 m/s	A
0,5 m/s	B (98,98%)
1 m/s	B (95,53%)
1,5 m/s	C (80,43%)
2 m/s	D
2,5 m/s	D

INSECT SCREEN

STANDARD	Stainless-steel mesh 2.3 x 2.3 mm	
OPTION	Stainless-steel mesh 6 x 6 mm	
	Stainless-steel mesh 20 x 20 mm	